Date: - 29<sup>th</sup> May, 2018

## Corrigendum

### For

# Tender for Mechanical Ventilator for the Department of Cardiology

NIT Issue Date : 20th April, 2018

NIT No. : Admn/Tender/236-2/2017-AIIMS.JDH

Pre-Bid Meeting : 01<sup>st</sup> May, 2018 at 04:00 PM

Earlier Last Date of Submission : 28<sup>th</sup> May, 2018 at 03:00 PM

Extended Last Date of Submission: 11th June, 2018 at 03:00 PM

Bid opening : 12<sup>th</sup> June, 2018 at 03:15 P.M

### The following revised and additional specification will be added:-

#### 1. Page No. 11, Point No. 06:

For

In-line Nebuliser with capability of producing < 3 micron drug particle...

**Read** Deleted

#### 2. Page No. 11, Point No. 12:

For

Should have the facility for ETCO2 measurement

Read

Should have the ETCO2 monitoring.

#### 3. Page No. 11, Point No. 13:

For

Should have battery backup at least for 1 hour.

#### Read

Should have battery backup atleast for 1 hour for both compressor and ventilator.

#### 4. Page No. 11, Point No. 17:

For

Should be supplied with 2 Silicon adult the 1 Pediatrics breathing, 1 imported humidifier and 2 ultrasonic nebulizers chambers

#### Read

Should be supplied with 2 Silicon adult breathing circuit, 1 pediatrics breathing circuit, 1 imported humidifier and 2 ultrasonic nebulizers chambers

#### 5. Page No. 13, After Point No. 24:

#### Added Pont no. 25:

Upgradable to any of the Advance modes like ASV/PAV+/NAVA/smart care. Price of upgradation should be quoted separately.

Price of upgradation should be quoted separately

The whole section "Anesthesia Machine with Integrated Monitor & Ventilator.

# 6. Page No. 12-13, The Monitor should have the following :- Point No. 01-15 h : For

The Monitor should have the following

- 1. A modular configurable patient monitor
- 2. Should have atleast 14"TFT colour display with up to 12 waveforms at a time.
- 3. Should be touch screen
- 4. Should be able to measure the following parameters:
- a) 3/5 lead ECG with electrocautery & amp; defibrillator filter with ST

Segment & amp; arrhythmia detection with analysis,

- b) Respiration, SpO2, temperature
- c) NIBP, 2 IBP, ETCO2
- d) Multi –Gas analysis with auto detection of all anesthetic agents
- e) Integrated BIS/entropy Monitoring.
- f) Upgradable to cardiac output ( thermodilution ) monitoring.
- 5. Should be able to automatically detect and calculate MAC of all anaesthetic gases.
- 6. Should be able to calculate and display FiO2.
- 7. Intelligent cooling system to keeps the unit running quiet during use.
- 8. Separate indicator lights for technical and physiological alarms.
- 9. Maximum BEEP tone should be loud enough to be audible from atleast a distance of 12 feet"s.
- 10. Should have graded audio and visual alarms for the following parameters:
  - a) Blood pressure High and Low
  - b) SpO2 High and Low
  - c) Heart rate High and Low
  - d) Respiration High and Low
  - e) FiO2 High and Low
- 11. Trends Upto 24 Hours or more, trend analysis, upto 24 hours full disclosure.
- 12. Battery Back- up Li-ion Battery of 1 hour or more.
- 13. The machine should be internationally reputed company and should be USFDA approved.
- 14. Bidder must ensure regular supply of Sodalime
- 15. The machine should be supplied with the following accessories:
  - a. ECG Cable 2 nos
  - b. Reusable SpO2 Sensors: 2 each for Adult, Pediatric & Samp; Neonatal.
  - c. NIBP Cuff: 2 each for Adult, Pediatric & Denatal.
  - d. IBP Transducers: Disposable 10 nos.
  - e. IBP Cable: 2 nos
  - f. BIS Electrode: 10 nos
  - g. ETCO2 Sample Line: 10 nos
  - h. Reusable autoclavable Breathing circuit: 2 nos each for Adult & pediatric.

#### Read

#### **Deleted**

## 7. Page No. 13, Point No. 15i:

For

Upgradable to any one of the Advance modes like ASV/ Auto flow/ PAV+/NAVA/ smart care.

Price of upgradation should be quoted separately.

The whole section "Anesthesia Machine with Integrated Monitor & Ventilator

Read

**Deleted**