# Invitation of quotation for Repairing of overhead water tanks on various buildings at AIIMS Jodhpur.

Inquiry No.
Inquiry Issue Date
Last Date of Submission

AIIMS Jodh./Engg./Q.N./2022-23/03 15 June 2022 22 June 2022 at 03:00 PM



## All India Institute of Medical Sciences, Jodhpur

Basni Phase - II, Jodhpur – 342005, Rajasthan Telefax: 0291- 2012978 www.aiimsjodhpur.edu.in



## ALL INDIA INSTITUTE OF MEDICAL SCIENCES, JODHPUR अखिल भारतीय आयुर्विज्ञान संस्थान, जोधपुर

Quot. No. AIIMS/Jodh./Engg./Q.N./2021-22/03

Dated: 15 June 2022

#### **QUOTATION NOTICE**

Sealed Quotations are invited from the vendors/supplier/contractor empanelled with CPWD, Railway, MES, Indian oil & specialized repair agencies by the undersigned on behalf of the Director, AIIMS Jodhpur for "Repairing of overhead water tanks on various buildings at AIIMS Jodhpur." Description of items and bill of quantities is given overleaf. Quotation should reach this office on or before 22 June 2022 up to 3:00 PM and the quotation will be opened on the same day at 3:30 PM in the presence of quotationers or their representative who want to be present.

#### **General Terms and Conditions:**

- 1. The quotations received after 22 June 2022 and unsealed shall not be entertained under any circumstances whatsoever. In case of postal delay this Institute will not be responsible. The offer Submitted Fax/Email shall not be considered and no correspondence will be entertained in this matter.
- 2. Quotations must be in the enclosed prescribed Performa on the letter head of the firm duly signed by the Proprietor/Partner/Director or their Authorized Representative, in case of signing of quotation by the authorized representative letter of authorization must be attached with the quotation. Quotation must be dropped in "Quotation Box" located in Administration Block of AIIMS, Jodhpur.
- 3. Rates must be quoted in "Indian Rupees" and as per the format specified taxes extra if any must be written separately.
- 4. Rates must be quoted FOR basis (including Freight charges, Insurance, installation etc.)
- 5. No overwriting or cutting is permitted in the rate. If found, the quotation shall be summarily rejected.
- 6. The rates quoted must be valid for 90 days minimum from the date of opening of the quotation.
- 7. Becoming L1 will not be the criteria for awarding of work unless the rates are reasonable & justified.
- 8. RTGS/NEFT details need to be furnished by the supplier with the quotation on the letterhead of supplier/firm/agency.
- 9. The firm/agency may satisfy the following conditions and attach self-attested copy of the same with the quotation:
  - The firm shall have valid GSTIN and IT PAN.
  - The firm should not be black listed by any Govt. Agency/Dept.
- 10. Quotations qualified by such vague and indefinite expressions such as "subject to prior confirmation", "subject to immediate acceptance" etc. will be treated as vague offers and rejected accordingly. Any conditional quotation shall be rejected summarily.
- 11. The time allowed for carrying out the above work is 45 days from the date of issue of work order.
- 12. If the supplier/vendor/contractor fails to carrying out the above work on or before the stipulated date, then a penalty at the rate of 0.5 % per week of the total order value shall be levied subject to maximum of 10% of the total order value.
- 13. Payment Terms: Payment will be only after satisfactory completion of work and after inspection by the AIIMS Jodhpur.
- 14. Disputes: In the event of any dispute or disagreement arising between the contractors and any other department of AIIMS Jodhpur with regards to the interpretation of "Terms & Conditions" of this inquiry, the same shall be referred to the Director, AIIMS Jodhpur whose decision will be final and binding upon the contractor.
- 15. AIIMS, Jodhpur reserves the right to increase or decrease quantity and /or amount of work. Decision of Quantity of work in the AIIMS, Jodhpur will be final in this regard.
- 16. AIIMS, Jodhpur reserves the right to reject any quotation or part or the whole of inviting quotation process without assigning any reason. Decision of the AIIMS, Jodhpur will be final in this regard.

#### **Special Terms & Conditions:**

1. Bidder must quote rate in Price Bid Form provided in Annexure-1 on the letterhead of the firm.

(Executive Engineer

# [On the letterhead of firm] ANNEXURE "A" Price Bid Form

To,
Executive Engineer,
AIIMS, Jodhpur.
Dear Sir.

1. I/We	Submitted the quotation for Inquiry No. AIIMS/Jodh./Engg./Q.N./2022-
23/03 at AIIMS Jodhpur".	

- 2. I/We thoroughly examined, understood and accepted terms & conditions given in the enquiry document, failing which my quotation will be rejected out rightly.
- 3. I/We hereby offer to supply at the following rates.

Painting with silicon & acrylic emulsion based water thinnable sealer of approved brand and manufacture on wet or patchy portion of plastered surfaces: two coats  Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade Old work (Two or more coats applied @ 1.43 ltr/ 10 sqm) over existing cement paint surface  Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline slurry shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the engineer-in-charge. The product performance shall carry guarantee for 10 years against any leakage. For vertical surface two coats @	S.No	Description of work	Unit	Total Qty.	Rate	Amount
of approved brand and manufacture on wet or patchy portion of plastered surfaces: two coats  Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade Old work (Two or more coats applied @ 1.43 ltr/ 10 sqm) over existing cement paint surface  Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline slurry shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the engineer-in-charge. The product performance shall carry guarantee for 10 years against any leakage. For vertical surface two coats @ 0.70 kg per sqm  Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requiremen	1	and the like by scrapping, sand papering and preparing the surface		416.00		
Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade. Old work (Two or more coats applied @ 1.43 ltr/ 10 sqm) over existing cement paint surface.  Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline slurry shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the engineer-in-charge. The product performance shall carry guarantee for 10 years against any leakage. For vertical surface two coats @ 0.70 kg per sqm  Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90%	2	of approved brand and manufacture on wet or patchy portion of		416.00		
Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline slurry shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the engineer-in-charge. The product performance shall carry guarantee for 10 years against any leakage. For vertical surface two coats @ 0.70 kg per sqm  5  Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic	3	Silicone additives of required shade Old work (Two or more coats	Sqiii	410.00		
Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic	4	nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline slurry shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the engineer-in-charge. The product performance shall carry guarantee for 10 years against any leakage. For vertical surface two coats @		223.00		
self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the engineer-in-charge. The product performance shall carry guarantee for 10 years against any leakage. For horizontal surface one coat	5	Providing and applying integral crystalline slurry of hydrophilic in nature for waterproofing treatment to the RCC structures like retaining walls of the basement, water tanks, roof slabs, podiums, reservior, sewage & water treatment plant, tunnels / subway and bridge deck etc., prepared by mixing in the ratio of 5 : 2 (5 parts integral crystalline slurry : 2 parts water) for vertical surfaces and 3 : 1 (3 parts integral crystalline slurry : 1 part water) for horizontal surfaces and applying the same from negative (internal) side with the help of synthetic fiber brush. The material shall meet the requirements as specified in ACI212-3R-2010 i.e by reducing permeability of concrete by more than 90% compared with control concrete as per DIN 1048 and resistant to 16 bar hydrostatic pressure on negative side. The crystalline slurry shall be capable of self-healing of cracks up to a width of 0.50mm. The work shall be carried out all complete as per specification and the direction of the engineer-in-charge. The product performance shall carry guarantee				

Total Amount in Figure (Including	GST & Taxes):		
Total Amount in words (Including	GST & Taxes):		
Date			
Place			
		Signature of Authorised Person:	
		Name of the Firm/Agency:	
		Phone No:	
Firm's GSTIN:			
Firm's PAN No:			
Bank Account No:			
Bank Name:			
Branch:	IFSC Code		